

ANTISTATIC PVC

**ANTISTATIC PVC \_ PVC ANTISTATIQUE \_ PVC ANTISTATICO**

available sizes \_ formato disponibile: **600 x 600 x 2,0 mm**



0003 ivory

0010 azure

0120 borneo

0108 pepper

0002 platinum

Other types of antistatic pvc parquet available on request \_ Altri tipi di pvc antistatico disponibili a richiesta

**description**

Total Thickness	EN ISO 24346 (EN 428)	mm	2.0
Weight	EN ISO 23997 (EN 430)	g/sq.m	3300
Width/Length of Sheet	EN ISO 24341 (EN 426)	cm/lm	200/20
Tile size	EN ISO 24342 (EN 427)	mm	300 x 300* / 608 x 608
Number of tiles per package	-	-	50/20

**classification**

Norm/Product Specification	-	-	EN ISO 10581 (EN 649)
European classification	EN ISO 10874 (EN 685)	class	34-43
Fire rating	EN 13 501-1	class	Bfl-s1
Static electrical propensity	EN 1815	kV	< 2

**performance**

Wear resistance	EN 660.2	mm <sup>3</sup>	7.5
Wear Group	NF 189	group	M
Type Binder content	EN ISO 10581	type	II
Dimensional stability	EN ISO 23999 (EN 434)	%	sheet 0.40 tile 0.25
Residual indentation	EN ISO 24343-1 (EN 433)	mm	0.03
Castor Chair test (type W)	ISO 4918 (EN 425)	-	OK
Thermal Conductivity	EN ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour Fastness	EN 20 105-B 02	degree	6
Surface Treatment	-	-	PUR
Chemical Products fastness	EN ISO 26987 (EN 423)	class	OK

**environment / indoor air quality**

TVOC after 28 days	ISO 16000-6	µg/ m <sup>3</sup>	< 10
--------------------	-------------	--------------------	------

**ce marking**



EN 14 041

-



\*upon special request

member\_socio



CBI EUROPE  
Via Mons. A.O. Romero, 14  
Località San Biagio  
60027 Osimo (AN) \_ Italy  
tel + 39 071 71 08 688

administration \_ amministrazione:  
fax +39 071 71 08 635  
order \_ ordini: fax +39 071 71 08 561  
info@cbi-europe.com  
www.cbi-europe.com